SALVAFIX

ENGLISH



Salvafix locks *have been designed for fixing belts and straps together introducing a pin though the eyelets and bloking it with the button cap. Can be only released when placing the magnetic key on the top of the button cap and pulling out.*

SVF3500 standard locks *are supplied in all Salvafix products. And are composed by the following parts:*

SVF3504 - Pin: *- stainless steel pin.*
SVF3503 - Button cap: *PC/ABS casing with internal mechanism.*

STANDARD LOCK


FEATURES



Magnetic release safety lock



High precision stainless steel pin



Strength max. 150Kg.

SPECIFICATIONS

PRODUCT FAMILY: SALVAFIX locks


PRODUCT NAME: Standard safety lock

INTENDED USE: Sealing system to fix Salvafix straps

BASIC UDI-DI: 843603535SVFNC

SIZE CHART

Ref.	Measures (mm)	
	Diameter	Height
SVF3500	Ø 28,8 mm	35 mm



COLOUR

Yellow

COMPOSITION

Pin: Stainless steel
Button cap: PC/ABS
Mechanism: Stainless steel/PES foam

PACKAGING

BOX 10 UNITS
- SVF3500 - SALVAFIX Standard Safety lock

BOX 20 UNITS
- SVF3503 - SALVAFIX Standard button cap
- SVF3504 - SALVAFIX Stainless steel 6mm pin

LAUNDRY INSTRUCTIONS



- Do not wash the Salvafix safety lock. Can not be submerged in any liquid. The entrance of liquids inside the button cap will cause malfunction of the locking systems.

ATTENTION



- Always remove the pin and button cap before laundering. Locks can be cleaned with a damp cloth using a disinfectant solution over the outer surface.

MEDICARE SYSTEM
MEDI CARE SYSTEM S.L.U.
C/ Abat Escarré 15 - 08302 Mataró SPAIN
Tel.: +34 937 570 048 - Fax: +34 937 414 068
E-mail: info@medisystemsl.com · www.medicaresystem.es

CE Declaration according to Regulation (EU)745/2017 of the European Parliament & Council

*This data sheet could be changed without prior notice

CE